

SQG CENTRAL ACCUMULATION AREA WEEKLY INSPECTION TOOL

Small quantity generators (SQGs) can use this tool to record observations made during weekly inspections of their hazardous waste central accumulation area. Keep completed tool on file for three (3) years. Contact BEP for free, confidential assistance with weekly inspections.

	YES	NO	REQUIREMENT	REGULATION
CONTAINER REQUIREMENTS			Accumulation start dates are ≤180 days old unless an extension has been approved by the state, or the accumulation start dates are ≤270 days old if shipped ≥200 miles offsite.	§262.16(b-d)
			The quantity of hazardous waste accumulated onsite is ≤6,000 kg (13,278 lbs).	§262.16(b)(1)
			Container is in good condition with no leaks, corrosion, or deterioration.	§262.16(b)(2)(i)
			Container is made of or lined with materials that are compatible with the waste.	§262.16(b)(2)(ii)
			Container is closed except when actively adding or removing waste; no open funnels.	§262.16(b)(2)(iii)(A)
			Container is not opened, handled, or stored in a way that would cause it to rupture or leak.	§262.16(b)(2)(iii)(B)
			Only compatible wastes are accumulated in the container, and the container is separated from nearby incompatible materials.	§262.16(b)(2)(v)
			Container is marked with the words "Hazardous Waste" and an indication of the hazards of the contents, such as its characteristics, pictograms, DOT hazard labeling, or others.	§262.16(b)(6)(i) (A-B)
			Container is marked with the accumulation start date.	§262.16(b)(6)(i)(C)
			Container is marked with the EPA Hazardous Waste Number.	NAC 444.8671
PREPAREDNESS AND PREVENTION			Area is maintained and operated to minimize the possibility of fire, explosions, or spills.	§262.16(b)(8)(i)
			 Area is equipped with the following emergency response equipment: Internal communications or alarm system for providing emergency instruction to staff; Communication device for summoning local emergency responders; Fire extinguishers, fire control, spill control, and decontamination equipment; Adequate water supply for fire suppression systems and foam producting equipment. 	§262.16(b)(8)(ii)
			Emergency equipment is tested and maintained to ensure it is functional.	§262.16(b)(8)(iii)
			Staff have immediate access to communication equipment when handling hazardous waste.	§262.16(b)(8)(iv)
			Adequate aisle space is provided for unobstructed movement of emergency personnel.	§262.16(b)(8)(v)
			Emergency information is posted next to telephones or in areas directly involved in the generation and accumulation of hazardous waste.	§262.16(b)(9)(ii)
			An attempt was made to make arrangements with local emergency responders; records of attempt(s) maintained on site.	§262.16(b)(8)(vi)
Notes on corrective actions taken for any items not in compliance:				
Inspector Name(s):				
Date:			Time:	

(800) 882-3233

help@unrbep.org

www.unrbep.org